

**SPECIFICATION** 

V	V		_[	) 	L	ı	=	
С	0	M	Р	U	Т	E	R	S

Model	Fastloc®	Depth	Temperature	Light Level	LxWxH(mm)	Weight (g)
TDR10-F-393	✓	✓	✓	Optional	105 x 56 x 30	213
TDR10-F-296	✓	✓	✓	Optional	85 x 85 x 27	210
TDR10-F-297	✓	✓	✓	Optional	86 x 55 x 26	165

<sup>1.</sup> The above estimated tag life relies on battery variability, temperature, power settings, features utilized, etc. Life estimates are calculated using manufacturers' specifications and assumes 250 transmissions per day and, where applicable, 24 Fastloc® acquisitions per day.

These tags all feature the latest Fastloc technology for improved satellite acquisition and maximized battery and tag duration. Some also incorporate tough urethane abrasion protection (body armor). This is a small representation of the wide variety of archival tags we offer. All tags shown include sensors for depth, temperature, and light level. There are other configurations available with different battery capacities and sensor combinations.







Model: TDR10-F-297

OTARIIDS/PHOCIDS ARCHIVAL FASTLOC®

8310 154th Ave NE, Suite 150 Redmond, WA, 98052 USA

This is a small representation of our available tags. Tag features and specifications subject to change without notice. Comparative scale is approximate. Argos antennas and sensor stalks not shown to length. © Wildlife Computers. All rights reserved.