

OTARIIDS/PHOCIDS ARCHIVAL FASTLOC® SPECIFICATION

Model	Fastloc®	Depth	Temperature	Light Level	LxWxH(mm)	Weight (g)	Life in Days ¹
TDR10-F-393	✓	✓	✓	Optional	105 x 56 x 30	215	1600
TDR10-F-296	✓	✓	✓	Optional	85 x 85 x 27	210	1600
TDR10-F-297	✓	✓	✓	Optional	86 x 55 x 29	132	800

^{1.} Lifespan estimates may increase or decrease based on your deployment. Please see your technical sales consultant.

These tags all feature the latest Fastloc* technology for improved satellite acquisition and maximized battery and tag duration. Some also incorporate tough urethane abrasion protection (body armor). This is a small representation of the wide variety of archival tags we offer. All tags shown include sensors for depth, temperature, and light level. There are other configurations available with different battery capacities and sensor combinations.



Model: TDR10-F-393



Model: TDR10-F-296



Model: TDR10-F-297

tags@wildlifecomputers.com WildlifeComputers.com +1 (425) 881-3048

8310 154th Ave NE, Suite 150 Redmond, WA, 98052 USA

This is a small representation of our available tags. Tag features and specifications subject to change without notice.

Comparative scale is approximate. Tags are not shown to scale. Lifespan estimates rely on programming, battery variability, temperature, power settings, features utilized, etc.

© Wildlife Computers. All rights reserved. This is proprietary information and not to be reproduced, copied, or shared without written permission.