

SPLASH: FASTLOC® GPS BACKMOUNT SPECIFICATIONS

Model	Argos	Fastloc [®]	Depth	Temperature	Light Level	Life (days) ¹	LxWxH(mm)	Weight (g)
SPLASH-F-391	✓	√	✓	✓	Optional	330	86 x 58 x 28	160

^{1.} Lifespan estimates may increase or decrease based on your deployment. Please see your technical sales consultant.

The newest addition to the SPLASH family! This tag is the first SPLASH tag that integrates with the Wildlife Computers Data Portal.

The Wildlife Computers Data Portal helps collect, prepare, and analyze the data returned from the tag—via Argos or the archive. Data are easily sorted, filtered, searched, uploaded, and shared. Learn more about the Wildlife Computers Data Portal on wildlifecomputers.com

These tags also feature the latest Fastloc* technology for improved satellite acquisition and maximized battery and tag duration.



tags@wildlifecomputers.com WildlifeComputers.com +1 (425) 881-3048

8310 154th Ave NE, Suite 150 Redmond, WA, 98052 USA

This is a small representation of our available tags. Tag features, colors, and specifications subject to change without notice.

Comparative scale is approximate. Tags and antennas are not shown to scale. Lifespan estimates rely on programming, battery variability, temperature, power settings, features utilized, etc.

© Wildlife Computers. All rights reserved. This is proprietary information and not to be reproduced, copied, or shared without written permission.