

SPLASH10: BASIC FASTLOC BACKMOUNT SUITE

SPI	ECI	L A	Ur	VI.

Model	Argos	Fastloc [®]	Depth	Temperature	Life (days) ¹	LxWxH(mm)	Weight (g)
SPLASH10-BF-296	✓	✓		✓	485	85 x 85 x 27	210
SPLASH10-BF-297	✓	✓		✓	240	86 x 55 x 29	132
SPLASH10-BF-385	✓	✓		✓	500	121 x 66 x 51	290
SPLASH10-BF-393	✓	✓		✓	485	105 x 56 x 30	218

^{1.} Life estimates may increase or decrease based on your deployment. Please see your technical sales consultant for more information.

These tags all feature the latest Fastloc* technology for improved satellite acquisition and maximized battery and tag duration. They also incorporate tough urethane abrasion protection (body armor) and robust nitinol antennas.



Model: SPI ASH10-BF-393



Model: SPI ASH10-BF-296



Model: SPLASH10-BF-385

Model: SPI ASH10-BF-297

tags@wildlifecomputers.com WildlifeComputers.com +1 (425) 881-3048

8310 154th Ave NE, Suite 150 Redmond, WA, 98052 USA

This is a small representation of our available tags. Tag features and specifications subject to change without notice. Comparative scale is approximate. Tags are not shown to scale. Lifespan estimates rely on programming, battery variability, temperature, power settings, features utilized, etc. © Wildlife Computers. All rights reserved. This is proprietary information and not to be reproduced, copied, or shared without written permission.