




SPLASH10: BASIC FASTLOC BACKMOUNT SUITE

SPECIFICATION

| Model | Argos | Fastloc [®] | Depth | Temperature | Life (days) ¹ | L x W x H (mm) | Weight (g) |
|-----------------|-------|----------------------|-------|-------------|--------------------------|----------------|------------|
| SPLASH10-BF-296 | ✓ | ✓ | | ✓ | 485 | 85 x 85 x 27 | 210 |
| SPLASH10-BF-297 | ✓ | ✓ | | ✓ | 242 | 86 x 55 x 29 | 132 |
| SPLASH10-BF-385 | ✓ | ✓ | | ✓ | 503 | 120 x 66 x 50 | 290 |
| SPLASH10-BF-393 | ✓ | ✓ | | ✓ | 485 | 105 x 56 x 30 | 218 |

1. The above estimated tag life relies on battery variability, temperature, power settings, features utilized, etc. Life estimates are calculated using manufacturers' specifications and assumes 250 transmissions per day and, where applicable, 24 Fastloc[®] acquisitions per day, extended.

These tags all feature the latest Fastloc[®] technology for improved satellite acquisition and maximized battery and tag duration. They also incorporate tough urethane abrasion protection (body armor) and robust nitinol antennas.



Model: SPLASH10-BF-393



Model: SPLASH10-BF-296



Model: SPLASH10-BF-385



Model: SPLASH10-BF-297

tags@wildlifecomputers.com
 WildlifeComputers.com
 +1 (425) 881-3048

8310 154th Ave NE, Suite 150
 Redmond, WA, 98052 USA

v. 19-07 3:4

This is a small representation of our available tags. Tag features and specifications subject to change without notice. Comparative scale is approximate. Tags are not shown to scale. © Wildlife Computers. All rights reserved.

To Learn More Call: +1 (425) 881-3048 or Email: tags@wildlifecomputers.com